





6-Lobe Pin



6-Lobe Pin - Raised Countersunk Machine Screw - A2 Stainless Steel



Dimensions (mm)

| | | |
|---|---|-------------|
|  | SCREW TYPE 6-LOBE PIN | M3.5 |
| | DIMENSIONS | |
| RAISED COUNTERSUNK HEAD |  | 6.4 |
| |  | 1.8 |

Material and Finish

Material: A2 Stainless Steel
Heat Treatment: None
Finish: Passivated

Part Numbers, Shear Toque & Box quantities

| GAUGE | LENGTH | | | | | | | | DRIVER SIZE |
|-------|----------|----------|----------|----------|----------|----------|----------|----------|-------------|
| | 12mm | 20mm | 25mm | 30mm | 35mm | 40mm | 50mm | 75mm | |
| M3.5 | RTRM3512 | RTRM3520 | RTRM3525 | RTRM3530 | RTRM3535 | RTRM3540 | RTRM3550 | RTRM3575 | T10 |


Additional Information

Patented Product: Hafren Fasteners
Installation: 6-Lobe Pin - see video
Removal: 2-Way Removable Screw

Hafren
security fasteners

6-Lobe Pin

- ✓ 6-Lobe drive with internal pin
- ✓ High torque drive
- ✓ Available in multiple heads & threads
- ✓ Stocked in the largest range available



Every effort has been made to ensure the accuracy of information provided in this datasheet. Hafren Fasteners cannot warrant the information however, expressly or implied, and any liability arising from it is expressly excluded. Customers must satisfy themselves as to the suitability of products and the technical information relating to them, and it is recommended that you conduct your own tests to establish suitability. All sizes shown are in mm without min and max tolerances and are guide sizes. Hafren Fasteners reserve the right to change/alter sizes without notice. This does not effect your statutory rights.